

Specification Sheet

Product:

- FlexScreen
- In-Jamb Mount
- Motorized and Manual Operation



Box 2612
Norcross, GA 30091
(888) 606-7325 or (770) 446-0054
Fax: (888) – 884-9667
www.flexbarrier.com

1.0 General

1.0 Summary

A. All FlexScreen Doors shall be manufactured by FlexBarrier Products, LLC. Furnished materials shall include screen mesh curtain (with wind load stiffeners and bottom pocket), guide tracks, mounting brackets, flap seal, operating mechanisms and any special components.

B. Work not provided by FlexBarrier Products, LLC, includes the design of and the material used for the preparation of the door openings. Also structural or miscellaneous iron work and finish painting.

2.0 Products

2.1 Materials

A. The door curtain shall be constructed from an open weave vinyl coated polyester mesh, scrim count 17 x 11. The door is made in horizontal sections that are divided by pockets containing wind load stiffeners. The sections are typically 2 feet high but can vary slightly depending on the overall door size.

B. The wind load stiffeners are typically 3/4" fiberglass rods. For openings greater than 10' wide, a 3/4" (16 gauge) galvanized tube is used for the wind load stiffeners.

C. The bottom pocket shall contain a 3/16 proof coil chain that will allow the bottom of the curtain to seal more evenly at the floor.

D. The guide tracks are extruded aluminum and have a 4" deep channel that guides the curtain during the "opening" and "closing" operation. (Note: In certain situations where there are width restrictions, a 2 3/4" deep channel may be used). There is a 1" mounting leg that is the part of the guide track that is used to attach this track to the wall via the wall clip. The guide tracks have a mill finish and will have Black/Yellow safety tape running the full height to make the guide tracks more visible. There is also a 6" cut made at the top of the guide track that allows the top of the channel to be flared out (in "Y" shape) to allow the curtain to feed more easily into the track.

E. The mounting brackets consist of a commercial bracket that is mounted to each side of the jamb and is used attach the curtain barrel/tube inside the jamb.

F. The flap seal consists of a 1 1/2" piece of aluminum angle that is mounted to the header. A 14" flap is attached to the angle with velcro. This flap extends the width of the door opening and seals the gap between the top of the header and the mounted screen system.

G. Available operating mechanisms include an In-Tube Motor (model varies depending on door size). The motor will be provided with a maintain switch, power cord, switch box and switch plate. There is also a manual model that includes a Spring Loaded Tube that is limited to door openings up to 10' x 10'.

2.2 Operation

A. Motorized door systems will require a power source of 115 volts and will operate with a wall switch.

3.0 Execution

3.1 Installation

A. A qualified door dealer or their representative shall install all FlexBarrier FlexScreen doors.

3.2 Warranty

A. All FlexBarrier FlexScreen products are guaranteed to be of good quality and free from defect in material and workmanship for a period of 1-year from the date of purchase.