

Description: **SDPC-2S-LC-P33**

PRODUCT SPECIFICATIONS
SAVE-T PVC FILM

| Roll Size | | | |
|--|-----------------------|------|-------------|
| THICKNESS: | 12MIL +/- 5% | | |
| WIDTH: | 54" + 1/4" - 0" | | |
| LENGTH: | 96 YARDS | | |
| NET WEIGHT: | 100 LBS.* +/- 3% | | |
| YARD YIELD: | .96 | | |
| Material Description | | | |
| FINISH: | SUPER DOUBLE POLISHED | | |
| HAND: | SOFT - 2S | | |
| COLOR: | CLEAR | | |
| Special Features | | | |
| MVSS-302 FIRE RATING | | | |
| UV STABILIZED | | | |
| LOW COHESION | | | |
| - 15° F COLD CRACK | | | |
| Physical Properties | | | |
| Tensile Strength (PSI) | MD | 3100 | ASTM-D-882 |
| | CD | 3000 | |
| Elongation (%) | MD | 200 | ASTM-D-882 |
| | CD | 220 | |
| Tear Strength (Lbs./in) | MD | 385 | ASTM-D-1004 |
| | CD | 385 | |
| Heat Shrinkage (%) | MD | -6 | ASTM-D-1004 |
| | CD | +2 | |
| Shipped in a box, rolled in craft paper on 3" I.D. Cores | | | |

* Shipping weight : Add 12 lbs to net weight

Note: The information contained herein is believed to be reliable but no representations, guarantees or warranties of any kind are made as to its accuracy or suitability for particular applications.

TMI incorporated
5350 Campbells Run Road
Pittsburgh, PA 15205-9738
Web-Site: www.tmi-pvc.com

Toll Free: 800-888-9750
Phone: 412-787-9750
Fax: 412-787-3665
E-mail: customer-service@tmi-pvc.com