
PRODUCT SPECIFICATION SHEET

SAVE-T PVC 10 OZ COATED POLYESTER

TYPICAL TECHNICAL PROPERTIES	
BASE FABRIC	POLYESTER
THICKNESS	0.37 M/M
YARN (DENIER)	1000 * 1000, FLAT
THREADS (FD/ INCH)	20/20
TYPE OF COATING	E-PVC
WEIGHT (gr./ sq.m)	350
UV STABILIZED	YES
PHYSICAL PROPERTIERS	
TENSILE STRENGTH FS5102 (STRIP METHOD)	440 /415 LBS/2"
ELONGATION FS 5102	21 / 24 %
TEAR STRENGTH FS 5134 (TONGUE METHOD)	60 /50 Lbs
ADHESION STRENGTH FS 5970 (BOND)	15 Lbs/ 2"
HYDRO-STATIC RESISTANCE ASTMD-751A	440 P.S.I.
STANDARD ROLL DATA	
SIZE – YARDS	100
COLD CRACK	-30°C

Note: The information contained herein is believed to be reliable but no representations, guarantees or warranties of any kind are made as to its accuracy or suitability for particular applications.

TMI incorporated
 5350 Campbells Run Road
 Pittsburgh, PA 15205-9738
 Web-Site: www.tmi-pvc.com

Toll Free: 800-888-9750
 Phone: 412-787-9750
 Fax: 412-787-3665
 E-mail: customer-service@tmi-pvc.com