

---



---

## **PRODUCT SPECIFICATION SHEET**

### **SAVE-T PVC 14 OZ COATED POLYESTER**

<b>TYPICAL TECHNICAL PROPERTIES</b>	
BASE FABRIC	POLYESTER
THICKNESS	0.42 M/M
YARN (DENIER)	1000 * 1000, FLAT
THREADS (FD/ INCH)	16/ 16
TYPE OF COATING	E-PVC
WEIGHT (gr/sq.m)	470
UV STABILIZED	YES
<b>PHYSICAL PROPERTIES</b>	
TENSILE STRENGTH FS5102 (STRIP METHOD)	370 / 300 LBS/ 2"
ELONGATION FS 5102	21 / 25
TEAR STRENGTH FS 5134 (TONGUE METHOD)	25 / 25 Lbs
ADHESION STRENGTH FS 5970 (BOND)	15 Lbs/ 2"
HYDRO-STATIC RESISTANCE ASTMD-751A	400 P.S.I.
ABRISION RESISTANCE ASTM D 3884-92 (LOSS WEIGHT)	0.070 gr
<b>STANDARD ROLL DATA</b>	
SIZE – YARDS	100
COLD CRACK	-40°C (-40F)
OPERATION TEMPERATURE	MIN -20C (-4F) , MAX 80C (176 F)

Note: The information contained herein is believed to be reliable but no representations, guarantees or warranties of any kind are made as to its accuracy or suitability for particular applications.

---

**TMI incorporated**  
 5350 Campbells Run Road  
 Pittsburgh, PA 15205-9738  
 Web-Site: [www.tmi-pvc.com](http://www.tmi-pvc.com)

Toll Free: 800-888-9750  
 Phone: 412-787-9750  
 Fax: 412-787-3665  
 E-mail: [customer-service@tmi-pvc.com](mailto:customer-service@tmi-pvc.com)