

---



---

## **PRODUCT SPECIFICATION SHEET**

### **SAVE-T PVC 22 OZ COATED POLYESTER**

<b>TYPICAL TECHNICAL PROPERTIES</b>	
BASE FABRIC	POLYESTER
THICKNESS	0.64 M/M
YARN (DENIER)	1300 * 1300, ROUND
THREADS (FD/ INCH)	18/ 18
TYPE OF COATING	E-PVC
WEIGHT (gr./ sq.m)	750
UV STABILIZED	YES
<b>PHYSICAL PROPERTIES</b>	
TENSILE STRENGTH FS5102 (STRIP METHOD)	640 / 615 LBS/2"
TEAR STRENGTH FS 5134 (TONGUE METHOD)	100 / 90 Lbs
ADHESION STRENGTH FS 5970 (BOND)	20 Lbs/ 2"
HYDRO-STATIC RESISTANCE ASTMD-751A	750 P.S.I.
<b>STANDARD ROLL DATA</b>	
SIZE – YARDS	100
COLD CRACK	-40°C (-40F)
OPERATION TEMPERATURE	MIN -20C (-4F) , MAX 80C (176 F)

Note: The information contained herein is believed to be reliable but no representations, guarantees or warranties of any kind are made as to its accuracy or suitability for particular applications.

---

**TMI incorporated**  
 5350 Campbells Run Road  
 Pittsburgh, PA 15205-9738  
 Web-Site: [www.tmi-pvc.com](http://www.tmi-pvc.com)

Toll Free: 800-888-9750  
 Phone: 412-787-9750  
 Fax: 412-787-3665  
 E-mail: [customer-service@tmi-pvc.com](mailto:customer-service@tmi-pvc.com)