

Toll Free
800-888-9750



Materials Safety
Data Sheet
(MSDS)

Standard Grade Clear Flexible PVC Panel

FCS: Flat Clear Standard

All materials are:
CSFM Fire Rating, UV Stabilized,
– 0° F to 150° F, 79 Shore A Hardness

Click for Specifications → [SPEC](#)



SAVE-T® PVC

- Most Items are in Stock for Immediate Delivery
- Consult TMI for Samples
- Call for Specific Details

Panel Width	Model No.	Thickness	Roll Length	Shipping Weight
36"	FCS36275	9/32"	60'	315 Lbs.
	FCS36400	3/8"	60'	450 Lbs.
	FCS36500	1/2"	60'	540 Lbs.
40"	FCS40400	3/8"	60'	500 Lbs.
	FCS40500	1/2"	60'	600 Lbs.
45"	FCS45400	3/8"	60'	565 Lbs.
48"	FCS48275	9/32"	60'	420 Lbs.
	FCS48400	3/8"	60'	600 Lbs.
	FCS48500	1/2"	60'	720 Lbs.
60"	FCS60275	9/32"	60'	525 Lbs.
	FCS60400	3/8"	60'	750 Lbs.
	FCS60500	1/2"	60'	900 Lbs.

* Listed are commonly stocked items only. All sizes are not shown.

Special Orders

Custom Roll Sizes
from .040" to .500" thick
& from 3" to 60" wide

Available Converting Services

- Cutting to Size
- Normalizing

Toll Free
800-888-9750

International
412-787-9750

TMI, LLC © 2007

Vinyl Solutions
a division of TMI, LLC

5350 Campbells Run Road
Pittsburgh, PA 15205-9738

• fax: 412-787-3665 • web: www.tmivinylsolutions.com • e-mail: vinylsolutions@tmi-pvc.com

