

Toll Free  
800-888-9750



Materials Safety  
Data Sheet  
(MSDS)

## USDA Low Temp Clear Flexible PVC Panel (Yellow Tinted)

FCL: Flat Clear Low Temp

All materials are:  
CSFM Fire Rating, UV Stabilized,  
- 20° F to 140° F, 70 Shore A Hardness

Click for Specifications → [SPEC](#)



**SAVE-T® PVC**

- Most Items are in Stock for Immediate Delivery
- Softer Compounds for Use in Freezer Applications
- Consult TMI for Samples
- Call for Specific Details

Panel Width	Model No.	Thickness	Roll Length	Shipping Weight
36"	FCL36275	9/32"	60'	315 Lbs.
	FCL36400	3/8"	60'	450 Lbs.
40"	FCL40400	3/8"	60'	500 Lbs.
	FCL40500	1/2"	60'	600 Lbs.
45"	FCL45400	3/8"	60'	565 Lbs.
48"	FCL48275	9/32"	60'	420 Lbs.
	FCL48400	3/8"	60'	600 Lbs.
	FCL48500	1/2"	60'	720 Lbs.
60"	FCL60275	9/32"	60'	525 Lbs.
	FCL60400	3/8"	60'	750 Lbs.
	FCL60500	1/2"	60'	900 Lbs.

\* Listed are commonly stocked items only. All sizes are not shown.

### Available Converting Services

- Cutting to Size
- Normalizing

### Special Orders

Custom Roll Sizes  
from .040" to .500" thick  
& from 3" to 60" wide

- ◀ Main Menu
- ◀ Grade Menu

Toll Free  
800-888-9750

International  
412-787-9750

TMI © 2007

**Vinyl Solutions**  
a division of TMI, LLC

5350 Campbells Run Road  
Pittsburgh, PA 15205-9738

• fax: 412-787-3665 • web: [www.tmivinylsolutions.com](http://www.tmivinylsolutions.com) • e-mail: [vinylsolutions@tmi-pvc.com](mailto:vinylsolutions@tmi-pvc.com)

