



Description: 3054-UCMG-3S-LC-M23-38

PRODUCT SPECIFICATIONS

SAVE-T PVC FILM

Roll Size			
THICKNESS:	30MIL +/- 5%		
WIDTH:	54" + 1/4" - 0"		
LENGTH:	38 YARDS		
NET WEIGHT:	100 LBS.* +/- 3%		
YARD YIELD:	.38		
Material Description			
FINISH:	SUPER DOUBLE POLISHED		
HAND:	SOFT - 3S		
COLOR:	CLEAR		
Special Features			
MARINE GRADE - MILDEW RESISTANT			
ULTRA CLEAR			
UV STABILIZED - 1200 HOURS			
-15°F COLD CRACK			
LOW COHESION			
Physical Properties			
Tensile Strength (PSI)	MD	2700	ASTM-D-882
	CD	2550	
Elongation (%)	MD	240	ASTM-D-882
	CD	260	
Tear Strength (Lbs./in)	MD	330	ASTM-D-1004
	CD	330	
Heat Shrinkage (%)	MD	-5	ASTM-D-1004
	CD	+2	
Shipped in a box, rolled in craft paper on 3" I.D. Cores			

* Shipping weight : Add 12 lbs to net weight

Note: The information contained herein is believed to be reliable but no representations, guarantees or warranties of any kind are made as to its accuracy or suitability for particular applications.

TMI International, LLC
 5350 Campbells Run Road
 Pittsburgh, PA 15205-9738
 Web-Site: www.tmi-pvc.com

Toll Free: 800-888-9750
 Phone: 412-787-9750
 Fax: 412-787-3665
 E-mail: customer-service@tmi-pvc.com