



PRODUCT SPECIFICATIONS

SAVE-T PVC Coated Polyester Fabric

18.5 OZ

Spec Sheet # 06.22.11.JI

Material Description						
Roll Dimensions		English		Metric		
Material Weight		18.5 oz/yd ²		630 g/m ²		
Roll Width		61"		154.9cm		
Roll Length		100 yards		91.44 meters		
Base Fabric						
Fiber		Polyester				
Yarn (Denier)		1100*1430		-		
Fabric Count (threads)		18/17 (td/inch)		-		
Physical Properties						
				Test Method		
		Metric	English	FS-191	BS	DIN
Breaking Strength	Warp	2500 N/5cm	570 lb/2in	FS 5100	BS 3424 method	DIN 53354
	Weft	2200 N/5cm	502 lb/2in			
Tear Strength	Warp	373 N/5cm	85 lb/2in	FS 5134	BS 3424 method	DIN 53363
	Weft	373 N/5cm	85 lb/2in			
Adhesion Strength		90 N/5cm	21 lbs/2"	FS 5970	BS 3424 method	DIN 53357
Temperature Resistance		-30 ~ +70°C	-22 ~ +160°F	-	ASTM D 2136	DIN 53361
UV Stabilized		For Exterior Applications				
Mildew Resistance		For Exterior Applications				
Optional		3P - Phthalate Free				

Note: The information contained herein is believed to be reliable but no representations, guarantees or warranties of any kind are made as to its accuracy or suitability for particular applications.

TMI, LLC
 5350 Campbells Run Road
 Pittsburgh, PA 15205-9738
 Web-Site: www.tmivynilsolutions.com

Toll Free: 800-888-9750
 Phone: 412-787-9750
 Fax: 412-787-3665
 E-mail: vinylsolutions@tmi-pvc.com