



# PRODUCT SPECIFICATIONS

## SAVE-T PVC Coated Polyester Fabric

### 13 OZ LAMINATED

Spec Sheet # 13L-3-07

Material Description						
Roll Dimensions		English		Metric		
Material Weight		13 oz/yd <sup>2</sup> (+/- 4%)		440 gr/sq.m (+/-4%)		
Roll Width		61"		154.9cm		
Roll Length		100 yards		91.44 meters		
Net Weight		138 lbs		62.7 kg		
Base Fabric						
Fiber		Polyester				
Thickness		.019"		0.48 m/m		
Yarn ( Denier)		840*840		-		
Fabric Count (threads)		9/9 (fd/inch)		-		
Type of Coating		S-PVC				
Physical Properties						
				Test Method		
		English	Metric	FS-191	ASTM	DIN
Tensile Strength (Strip Method)	Warp	185 lbs/2"	84.1 kg/5cm	FS 5102	ASTM D 5035	DIN 53354
	Fill	167 lbs/2"	75.9 kg/5cm			
Tear Strength (Tongue Method)	Warp	40 lbs	18.2 kg	FS 5134	ASTM D 2261	DIN 53356
	Fill	43 lbs	19.5 kg			
Adhesion Strength		22 lbs/2"		FS 5970	ASTM D 2724	
Temperature Resistance		-22 ~ +160°F	-30 ~ +70°C	-	ASTM D 2136	DIN 53361
Special Features		UV For Exterior Applications, Mildew Resistant NFPA-701 Fire Rated				

Note: The information contained herein is believed to be reliable but no representations, guarantees or warranties of any kind are made as to its accuracy or suitability for particular applications.

**TMI, LLC**  
 5350 Campbells Run Road  
 Pittsburgh, PA 15205-9738  
 Web-Site: [www.tmivinylsolutions.com](http://www.tmivinylsolutions.com)

Toll Free: 800-888-9750  
 Phone: 412-787-9750  
 Fax: 412-787-3665  
 E-mail: [vinylsolutions@tmi-pvc.com](mailto:vinylsolutions@tmi-pvc.com)